



Publication number : **0 543 588 A2**

⑫

EUROPEAN PATENT APPLICATION

⑳ Application number : **92310415.2**

㉑ Int. Cl.⁵ : **G06F 9/44**

㉒ Date of filing : **16.11.92**

㉓ Priority : **21.11.91 US 796098**

㉔ Date of publication of application :
26.05.93 Bulletin 93/21

㉕ Designated Contracting States :
DE FR GB

㉖ Applicant : **International Business Machines Corporation**
Old Orchard Road
Armonk, N.Y. 10504 (US)

㉗ Inventor : **Lang, Andrew Joseph**
17645 Holiday Drive
Morgan Hill, California 95037 (US)
Inventor : **Shannon, Alfred William**
830 La Crosse Drive
Morgan Hill, California 95037 (US)

㉘ Representative : **Killgren, Neil Arthur**
IBM United Kingdom Limited Intellectual
Property Department Hursley Park
Winchester Hampshire SO21 2JN (GB)

㉙ **Generating and processing computer programs.**

㉚ Method and means are described which provide a way for an application program to be generated to include dependency control blocks which indicate which support programs must be initialized in the run-time support environment prior to the application program's initialization and which must be terminated after its termination. Since support programs may be dependent on each other, a topological sort is performed to determine an order in which the support programs can be initialized so that no routine is initialized before all of its prerequisites are initialized. The initialization order is saved, so that following the execution of the program, termination can be performed in the reverse order.




FIG. 1

Technical Field

The present invention relates to generating and processing computer programs.

Various high level languages are in wide use for computer programming, e.g., C, COBOL, FORTRAN, PL/I, PASCAL, etc. Computer programs may be written in more than one of these languages. Execution of programs written in these languages normally requires that language specific run-time support code be present and initialized to enable the code produced by the respective compilers to function correctly. It is desirable to allow for the language specific run-time support code to be written in multiple languages, but this presents special problems. Termination ordering also presents similar problems.

During initialization and termination of a multi-language application program, language specific initialization and termination routines are called for each language in the application. When the language specific routine for a particular language requires support provided by a second language then the second language's support must be initialized before the first language's support is initialized and terminated only after the first language's support has been terminated.

The idea of ordering based on dependencies is known. Knuth, for example, describes the problem in The Art of Computer Programming, Vol. 1, Addison-Wesley, 1975, pages 258-265. Knuth describes the problem of topological sorting of a set on which a partial ordering is defined. The goal is to find a linear sequence of the members of the set such that any item in the sequence will precede another in the sequence if the one is defined to precede the other in the partial ordering. Knuth describes an algorithm for topological sorting.

The problem of initialization ordering is related to topological sorting. The dependency that one language has upon the initialization of another defines a partial ordering between the languages. The problem is to find an order to initialize languages in a multi-language application so that for any language in the application, all languages that it depends upon are initialized by the time it must be initialized. Termination can then be performed in the reverse order.

It is also possible for programs to have dependencies on support programs which are unrelated to language support as such. Dependency on a debugging program would be an example of this.

It is conventional in the computer science field to use control blocks (sometimes called headers) containing non-executable code to convey information needed to execute a program. Control blocks which give initial information about a program are sometimes called program headers.

The term "application program" (or simply "application") will be used to include both end-user developed computer programs and computer programs which are sometimes called system programs, such as compilers. For convenience, the term "program" will be used to include routines or modules which in other contexts might not be considered to be programs. Thus, language specific run-time support routines will be called programs even though they may be inherently incapable of independent execution.

According to the invention there is provided a method of generating object code for inclusion in a computer program having executable object code comprising the steps of: forming a dependency control block (DCB) object code having a selected symbolic name; writing in the DCB object code data representative of prerequisite programs on which the executable object code is dependent; and storing the DCB object code together with the executable object code; thereby, creating first object code.

There is further provided a system for generating object code for a computer program having executable object code comprising: means for forming a dependency control block (DCB) object code having a selected symbolic name; means for writing in the DCB object code data representative of prerequisite programs on which the executable object code is dependent; and means for storing the DCB object code together with the executable object code; whereby first object code can be created.

The control blocks may then be used to indicate which support programs must be initialized in the run-time support environment prior to the application program's initialization, permitting the initialization and termination of prerequisite programs, including language specific support routines, for a single or multi-language application that will satisfy the dependencies. In an embodiment to be described below, a set of control blocks is defined which is associated with an application program. These control blocks contain information which allows a common run-time initialization routine to ascertain the prerequisites upon which the application depends. The object code for application programs is generated to include object code forming one or more dependency control blocks (DCBs) together with executable object code produced by a compiler or assembler. Each DCB can contain information specific to the compiler, assembler or other program which generated associated executable object code. The DCB lists the prerequisite programs on which the executable object code depends. The object code for the DCB is preferably given a symbolic name for subsequent reference by a linkage editor. The DCBs may be implicitly associated with a language or other support program, so that there is no need to explicitly declare the associated language in its dependency list. The executable object code with its DCBs is preferably linked together with object code produced by other programs with their associated DCBs.

The initialization of the application program requires reading all of the DCBs included in the application program to determine all prerequisite language support and other routines needed by the application. The order of initialization of prerequisite routines is determined by performing a topological sort using the inter-dependencies to obtain an order in which initialization can occur such that no routine is initialized before all of its prerequisites are initialized. The initialization order is saved, so that following the execution of the application program termination can be performed in the reverse order.

The run-time environment initialization program must be able to locate all of the DCBs included in an application program. This is conveniently effected in the preferred embodiment by including in a program header the address of a language list which in turn contains the addresses of all of the DCBs.

In order that the invention may be well understood, an embodiment thereof will now be described with reference to the accompanying drawings, in which:-

Figure 1 illustrates the process of preparing application program object code containing a dependency control block (DCB).

Figure 2 illustrates the process of forming a DCB.

Figure 3 illustrates the process of forming a language list referencing all possible DCBs.

Figure 4 illustrates the process of initializing the support programs for a program containing DCBs.

Figure 5 illustrates the structure of a system for initializing the support programs for a program containing DCBs.

Figure 6 illustrates the structure of a system for creating DCBs and combining them with executable object code.

The invention is preferably implemented as a part of a larger common run-time environment, which will be called the Common Execution Environment (CEE) for system and application programs which may be written in multiple High-Level Languages (HLL). The invention is suitable for use on any size computer from mainframes to personal computers. CEE consists of common services which can be shared by all programs regardless of the language in which they are written. The system library available to the user also includes language specific support routines (LSRs), and other support programs which collectively will be called support programs. The invention is independent of operating systems and programming languages and can be applied to any multi-language run-time environment.

When an application begins executing, it must first initialize CEE before it can use any of the CEE provided services. This can be effected through any standard means of transferring program control. In the detailed embodiment it is done by calling an arbitrary external symbolic label reserved for use by CEE and passing information in registers which allows CEE to find the program header. When the application completes, it invokes the termination service of CEE in a similar manner. When CEE begins, it first initializes the common services, then, for each language in the application, it determines the LSR for that language. Only the LSRs required by the application are initialized. Similarly, during termination, CEE first terminates the LSRs and then the common services.

An LSR can be written in any language within certain restrictions. The LSRs can take advantage of common CEE services, since they are initialized before language specific components. But the LSR cannot, in general, take advantage of features of the language in which it is written unless that language is already initialized. For example, if the language specific support routines for COBOL were written in C, then initialization for applications that include COBOL routines would have to include initializing the C specific support routines first. The prior art does not teach a way to communicate this type of dependency to a common initialization program. Similarly requiring debugging support might require that LSRs be initialized to support the code in the debugger.

To solve this problem a means is provided for compilers for each language used in an application to indicate which other LSRs and support routines must be initialized prior to its initialization. The full list of support routines needed by an application is determined along with each one's dependencies, then a topological sorting method is used to determine an initialization order that will satisfy the dependencies as indicated by each control block.

For each language required by a multi-language application, a language specific control block is statically bound with the application. These can be accessed by CEE during initialization by way of the parameters passed to CEE initialization routine. Each language specific component in CEE is identified by a unique member identifier. Within each of the language specific control blocks is a table of member identifiers indicating which support programs must be initialized before that member can be initialized. Thus, during initialization, CEE can determine the dependencies between all the languages in the application.

Figure 1 shows the process of preparing object code containing a control block which lists the programs on which then executable object code is dependent. This control block will be called the dependency control block (DCB). The support code library 115 consists of executable object code for language specific support

routines or other programs which might be typically stored on non-volatile storage, e.g., disk drives, for repeated subsequent use. The language list 116, which is shown in detail in Table 4, is used to create a table of addresses for all of the DCBs contained in the final program 118. Only one DCB is shown and is labelled DCB-x.117, but in practice there will be multiple DCBs. The support code, language list, and the DCBs are produced using standard compilers and/or assemblers 111. The user uses the compilers and/or assemblers to create custom object code with an associated program header 112. A general purpose program header may be used or a program header specific to the compiler may be used, but in either case it is typically pre-compiled and included in the library. The user code is then combined with executable code from the library along with the language list and the appropriate DCBs through the use of a standard linkage editor 114 to produce the user's program 118 which consists of linked executable object code, the non-executable code of the program header, the language list, and the DCBs. The program header contains a pointer to the language list which in turn has a pointer to the DCB.

Figure 2 describes the steps of preparing executable object code and an associated DCB. Compiling the executable object code 121 is done according to the prior art practice. The forming of the DCB 122 is achieved by compiling or assembling source code, such as is shown in Table 2, to produce an object module which has an external symbolic name and contains data representative of the prerequisite programs on which the executable object code is dependent. Since it will normally be the case that the executable code and the DCB will be part of a collection of programs which will be used repeatedly over a long period of time, they should be stored 123 together on non-volatile storage such as a disk drive. If the information about the dependencies of the executable object code are known prior to compilation, the DCB may be created first.

The language list acts to create a list of all of the DCBs that ultimately are combined into a single program. Any mechanism which allows the CEE to locate all of the DCBs will work. Applicants' Detailed embodiment described herein uses a language list which is a separate object module. In another embodiment the function of the language list could be combined into the program header, for example. Figure 3 shows the process of creating the language list. Source code for the language list, such as is shown in Table 4, is prepared 126, compiled or assembled 127 and stored for repeated subsequent use 128.

After CEE has initialized the common services component, it initializes all language specific components or members in the application using the method described in pseudo-code in Table 1. By virtue of the loop in lines 10-14 all required support programs for the application will be initialized. By virtue of the first **when** clause 17, a member support program is not initialized until all members it depends upon are initialized. By virtue of the second **when** clause 25, if there is a member with a dependency directly or indirectly upon itself (a circular dependency), it will be detected.

Satisfying termination dependencies is a similar problem. A support program must terminate before any support program that it depends upon. To solve this problem, the initialization order is saved in memory for use at termination time. The support programs are terminated in the reverse order from initialization.

```

10 mark all members uninitialised
11 for each member M, required by the application
12     call Initialize Member (M)
13 end for
14 exit

10      /*****
      /* Initialize Member logic. */
15 Initialize Member (M)
16     select
17         when M is uninitialised
18             mark M initializing
19             for each member M' on which M depends
20                 call Initialize Member (M')
21             end for
22             initialize M
23             mark M initialized
24             record the order in which M was initialized
25         when M is initializing
26             handle error: cyclic dependency
27         when M is initialized
28             nop
29     end select
30     return
31 end

```

Table 1

The form of the control block which lists dependencies is not critical. Any format may be substituted that provides the same dependency information. In the detailed embodiment described herein in detail, the control block is statically linked into the application, but in an alternative embodiment, it may be provided dynamically and read at execution time.

The particular algorithm used to determine the order for member initialization is not critical so long as it meets the requirement of not initializing any program before all of its dependencies have been initialized. Any algorithm that will perform a topological sort will work. Languages may either be initialized as each member is placed in final sorted order, or the members may be first sorted and then initialized in their sorted order. What is important is that the members be initialized in topological sorted order.

In the detailed embodiment the members to be initialized are communicated to the initializing routine through a control block which contains non-executable code. Table 2 shows an example, in standard IBM assembler language, of a DCB listing three dependencies. At line 105 a unique four character string is used to identify the particular compiler or other program to which the DCB belongs. This association implicitly identifies the specific support routine for the compiler. If, for example, the CEESG004 DCB has been assigned to the REXX compiler, then CEE automatically knows that the LSR for REXX, if any exists, must be initialized before the application containing this DCB can be executed. The total number of dependencies is listed as three at line 108. The dependencies are listed at lines 113-115 as coded integers 1, 2, and 5. These numbers are arbitrarily assigned to correspond to certain programs or language specific components. Thus, "1" might correspond to C specific support, "2" to FORTRAN specific support and "5" to COBOL specific support. It is essential to the functioning of the described embodiment that a predetermined list of these codes be available so that each programmer creating a DCB will know what numerical codes to put in the DCB to correctly indicate the dependencies. An alternative embodiment could use codes that are self-defining by, for example, putting character strings in the list which give the full name of the program so that the initialization program can uniquely identify the program which it needs to load without further extrinsic information. Self-defining codes also have the advantage that they can be dynamically built and updated.

```

5 101 CEESG004 CSECT
102 CEESG004 AMODE ANY
103 CEESG004 RMODE ANY
104 * * * * *
105         DC      CL4'S004'
106         DC      H'23'          length of this csect
107         DC      H'1'          version
10 108         DC      H'3'          Number of dependent member IDs
109         DC      Y(DEPIDS-CEESG004) Offset to the first dep.member
ID
110         DC      XL4'0'          Reserved for member use
111         DC      XL4'0'          Reserved for member use
15 112 DEPIDS    EQU      *          List of ids dependent upon
113         DC      FL1'1'          Program assigned code '1'
114         DC      FL1'2'          Program assigned code '2'
115         DC      FL1'5'          Program assigned code '5'
20 116         END

```

Table 2

25 Each program requesting initialization must have a program header such as the one listed in Table 3. Any format of header will work. The only piece of information in this header used in the invention is the address of CEELLIST at x+40 which is the language list.

30

35

40

45

50

55

| | | | | |
|----|-------------|-------------|----------------|-----------------------------|
| 5 | | START | CSECT | |
| | | START | AMODE ANY | |
| | | START | RMODE ANY | |
| | 000000 | NOP | 0 | |
| | 000004 | NOP | Y | |
| | 000008 | STM | 14,12,12(13) | Save caller regs |
| 10 | 00000C | BALR | 3,0 | |
| | | USING | *,3 | |
| | 00000E | B | AROUND | Branch around signature |
| | 000012 - 17 | ... | | unrelated data |
| 15 | 000018 | DC | A(PLIST) | Point to PLIST |
| | 00001C | DC | CL8'START' | Eye-catcher |
| | 000020 | DC | H'0' | Reserved |
| | | AROUND | EQU * | |
| | | ... | | |
| | | member code | | |
| 20 | | ... | | |
| | x | PLIST | DS OF | |
| | x+00 | ... | | unrelated data |
| | x+10 | CXD | | |
| | x+14 | DC | H'-1' | |
| 25 | x+16 | DC | AL2(PLIST_LEN) | |
| | x+18 - 3C | ... | | unrelated data |
| | x+40 | DC | A(CEELLIST) | List of weak externals |
| | showing | * | | ...languages in load module |
| 30 | 0+44 | ... | | |
| | | PLIST_LEN | EQU *-PLIST | Length of Parm List |

Table 3

35

The format of the CEELLIST language list is shown in Table 4. The order of the entries in the language list in the detailed embodiment corresponds to the codes assigned for use in the DCBs, but the order is unimportant. CEELLIST can contain entries for programs other than language specific support routines. In the sample list in Table 4, the sixth entry in the list corresponds to a debugging program. Entries do not need to be assigned at all; thus, entry one is listed as unassigned. The DCB shown in Table 2 is labelled CEESG004 and corresponds to the fifth entry in the list. When DCB's with the proper labels are linked into a module with CEEBLLST the addresses of those DCB's present will be placed in the list by conventional linkage software. CEE will find zeroes in the list for all DCBs not present in the module. Using the DCB address CEE can then easily find the list of dependency codes and mark those requiring initialization for input into the topological sorting routine of Table 1. The "WXTRN" keyword is conventionally supported by assemblers and linkage editors for computers in IBM's System/370 family and is used to indicate a weak external reference. The linkage editor will attempt to link these external references, but will only issue a warning if they are not found.

50

55

```

CEEBLIST CSECT ,           CEE LANGUAGE LIST HEADER
CEEBLIST RMODE ANY
CEEBLIST AMODE ANY

...
* Start of the actual Language List
ENTRY CEELLIST
10 CEELLIST DS OD           CEE LANGUAGE LIST
    WXTRN CEESG000
    DC A(CEESG000) 00 unassigned
    WXTRN CEESG001
    DC A(CEESG001) 01 common services
    WXTRN CEESG002
15 DC A(CEESG002) 02 compiler-x
    WXTRN CEESG003
    DC A(CEESG003) 03 compiler-y
    WXTRN CEESG004
    DC A(CEESG004) 04 program-x
    WXTRN CEESG005
20 DC A(CEESG005) 05 compiler-z
    WXTRN CEESG006
    DC A(CEESG006) 06 compiler-j
    WXTRN CEESG007
25 DC A(CEESG007) 07 compiler-k
    WXTRN CEESG008
    DC A(CEESG008) 08 compiler-l
    WXTRN CEESG009
    DC A(CEESG009) 09 compiler-m
    WXTRN CEESG010
30 DC A(CEESG010) 10 compiler-n
    WXTRN CEESG011
    DC A(CEESG011) 11 Debugger
    WXTRN CEESG012
35 DC A(CEESG012) 12 compiler-o
    WXTRN CEESG013
    DC A(CEESG013) 13 compiler-p
    WXTRN CEESG014
    DC A(CEESG014) 14 compiler-q
    WXTRN CEESG015
40 DC A(CEESG015) 15 assembler
    WXTRN CEESG016
    DC A(CEESG016) 16 compiler-r
    DC A(0)         Dummy entry must contain X'00'
    DS OD           This boundary requirement is mandatory.
                    It is needed to save processing time
45 *
    when
    *
                    CEE is being initialized.
    LLISTEND DC A(0) MARK THE END OF LIST
                    END
50

```

Table 4

Figure 4 shows the steps executed by CEE in initializing an application program containing DCBs. First, all of the DCBs must be located and a list of all prerequisites is made 131. In the detailed embodiment this step requires first reading the program header to find the address of the language list, then using the language list to determine the number of DCBs present in the program and the location of each one. The topological

sort is performed 132 to find an order in which initialization can occur without violating any dependency relationship. The support programs are initialized in the order determined by the topological sort and the order is saved for later use 133. Control is returned to the application program 134. When its execution is completed, the application returns control to CEE to allow termination of the support programs. Each support program must have a defined mechanism for allowing CEE to initialize and terminate it. This is preferably done through a standard call and return mechanism. CEE terminates the support programs in the reverse order from the initialization order 135.

Figure 5 is a block diagram showing the overall structure and inter-relationships of the functional units required to initialize a program using DCBs. The locating and reading means 151 passes an unordered list of support programs to the topological sorting means 152. The generated sorted list is stored in memory 153, e.g., RAM or disk. The initialization means 154 uses the sorted list to determine which support programs are to be initialized from the library 115. The library is simply the collection of support programs which will typically be stored on disk. Control begins with the application program which must call CEE to activate the sequence. After initialization the application program regains control 155 until it is ready to request termination. The termination means 156 must have access to the previously stored sorted list.

Figure 6 is a block diagram of the functional units required to generate a DCB. A list of codes for the support programs 161 is used by the DCB generator 162 in conjunction with the executable object code 164 to generate the DCB 163 which encodes the dependencies. The DCB is then stored together with executable object code on non-volatile storage for subsequent use 165.

Some advantages that the invention has over prior art techniques are:

Components of a language runtime environment may themselves be written in a high level language or even multiple languages.

Only those language specific components of the runtime environment that are necessary for the execution of the application need be initialized thereby saving execution time.

When a routine is called in an application, it need not first check whether its language specific support is initialized, also saving execution time. :

The control block usage requires minimal or no changes to compilers.

Using the foregoing specifications the invention may be implemented using standard programming techniques. The resulting program(s) may be stored on disk, diskettes, memory cards, ROM or any other memory device. For execution the program may be copied into the RAM of the computer. One skilled in the art of computer science will easily be able to combine the software created as described with appropriate general purpose or special purpose computer hardware to create a system. While the detailed embodiment of the present invention has been illustrated in detail, it should be apparent that modifications and adaptations to that embodiment may occur to one skilled in the art without departing from the scope of the present invention as set forth in the following claims.

Claims

1. A method of generating object code for inclusion in a computer program having executable object code comprising the steps of:
 - (a) forming a dependency control block (DCB) object code having a selected symbolic name;
 - (b) writing in the DCB object code data representative of prerequisite programs on which the executable object code is dependent; and
 - (c) storing the DCB object code together with the executable object code; thereby, creating first object code.
2. The method of claim 1 further comprising the step of:
 - linking the first object code to a language list object code containing a plurality of external references to symbolic names, including the selected symbolic name, to place the address of the DCB object code in the language list object code; thereby, forming second object code.
3. The method of claim 2 further comprising the step of linking first and second object codes to a program header object code referencing a symbolic name for the language list, to place the address of the language list into the program header object code.
4. A method of processing a computer program comprising the steps of:

- (a) reading a plurality of dependency control blocks (DCBs) specifying prerequisite support programs; and
- (b) initializing the support programs in an order such that no support program is initialized until all of its prerequisite support programs have been initialized.

- 5 5. The method of claim 4 wherein the initializing step further includes the steps of:
 - (a) selecting a prerequisite support program M;
 - (b) if M is uninitialised, then marking M as initializing;
 - 10 (c) for each prerequisite support program M' on which M depends recursively executing the method beginning at step (b) using M' as M;
 - (d) initializing M;
 - (e) marking M as initialized; and
 - (f) returning to step (c) at the point of recursion, if in a recursion.
- 15 6. The method of claim 4 further including the step of recording an initialization order of the prerequisite support programs for use during termination.
7. The method of claim 6 further including the step of terminating the prerequisite support programs in a reverse order from the initialization order after the computer program has completed execution.
- 20 8. The method of claim 4 including the preparatory step of reading a program header to locate the DCB.
9. The method of claim 4 including the preparatory steps of:
 - (a) reading the address of a language list object code from a program header object code; and
 - (b) reading the addresses of the DCBs from a language list object code.
- 25 10. A system for generating object code for a computer program having executable object code comprising:
 - (a) means for forming a dependency control block (DCB) object code having a selected symbolic name;
 - (b) means for writing in the DCB object code data representative of prerequisite programs on which the executable object code is dependent; and
 - 30 (c) means for storing the DCB object code together with the executable object code; whereby first object code can be created.
11. The system of claim 10 further comprising means for linking the first object code to a language list object code containing a plurality of external references to symbolic names, including the selected symbolic name, to form second object code containing a DCB and a language list object code which contains the address of the DCB.
- 35 12. The system of claim 11 further comprising means for linking the second object code to a program header object code referencing a symbolic name for the language list, to place the address of the language list into the program header object code.
- 40 13. A system for processing a computer program comprising:
 - (a) means for reading a plurality of dependency control blocks (DCBs) specifying prerequisite support programs; and
 - 45 (b) means for initializing the support programs in an order such that no support program is initialized until all of its prerequisite support programs have been initialized.
14. The system of claim 13 wherein the reading means further includes means for reading numeric or character codes which uniquely identify the prerequisite programs.
- 50 15. The system of claim 13 further including means for recording an initialization order of the prerequisite programs for use during termination.
16. The system of claim 15 further including means for terminating the prerequisite programs in a reverse order from the initialization order after the computer program has completed execution.
- 55 17. The system of claim 13 further including means for reading a program header to locate the DCB.
18. The system of claim 13 further including:

- (a) means for reading the address of a language list object code from a program header object code;
and
(b) means for reading the addresses of the DCBs from a language list object code.

5

10

15

20

25

30

35

40

45

50

55







FIG. 1

FIG. 2FIG. 3

FIG. 4




FIG. 5




FIG. 6



11 Publication number: **0 543 588 A3**

12

EUROPEAN PATENT APPLICATION

21 Application number: **92310415.2**

51 Int. Cl.⁵: **G06F 9/44**

22 Date of filing: **16.11.92**

30 Priority: **21.11.91 US 796098**

43 Date of publication of application:
26.05.93 Bulletin 93/21

84 Designated Contracting States:
DE FR GB

88 Date of deferred publication of search report:
20.10.93 Bulletin 93/42

71 Applicant: **International Business Machines Corporation**
Old Orchard Road
Armonk, N.Y. 10504 (US)

72 Inventor: **Lang, Andrew Joseph**
17645 Holiday Drive
Morgan Hill, California 95037 (US)
Inventor: **Shannon, Alfred William**
830 La Crosse Drive
Morgan Hill, California 95037 (US)

74 Representative: **Burt, Roger James, Dr.**
IBM United Kingdom Limited Intellectual
Property Department Hursley Park
Winchester Hampshire SO21 2JN (GB)

54 **Generating and processing computer programs.**

57 Method and means are described which provide a way for an application program to be generated to include dependency control blocks which indicate which support programs must be initialized in the run-time support environment prior to the application program's initialization and which must be terminated after its termination. Since support programs may be dependent on each other, a topological sort is performed to determine an order in which the support programs can be initialized so that no routine is initialized before all of its prerequisites are initialized. The initialization order is saved, so that following the execution of the program, termination can be performed in the reverse order.




FIG. 1



European Patent
Office

EUROPEAN SEARCH REPORT

Application Number

EP 92 31 0415

| DOCUMENTS CONSIDERED TO BE RELEVANT | | | |
|---|---|--|---|
| Category | Citation of document with indication, where appropriate, of relevant passages | Relevant to claim | CLASSIFICATION OF THE APPLICATION (Int. Cl.5) |
| A | EP-A-0 321 000 (NEC) * column 6, line 6 - column 7, line 7 * * column 12, line 31 - column 13, line 19 * * claims 2,3; figure 12 * --- | 1-18 | G06F9/44 |
| A | SOFTWARE PRACTICE & EXPERIENCE. vol. 21, no. 4, April 1991, CHICHESTER, GB pages 375 - 390 W.W. HO ET AL. 'AN APPROACH TO GENUINE DYNAMIC LINKING' * page 377, line 7 - line 19 * * page 380, line 1 - page 384, line 13 * * figures 1-3 * --- | 1-18 | |
| P,X | IBM TECHNICAL DISCLOSURE BULLETIN. vol. 35, no. 4B, September 1992, ARMONK, NY, US pages 44 - 49 'INTER-LINKAGE FUNCTION INVOCATION METHOD' * the whole document * ----- | 1-4, 8-14, 17, 18 | |
| | | | TECHNICAL FIELDS SEARCHED (Int. Cl.5) |
| | | | G06F |
| The present search report has been drawn up for all claims | | | |
| Place of search THE HAGUE | | Date of completion of the search 27 AUGUST 1993 | Examiner JONASSON J.T. |
| <p>CATEGORY OF CITED DOCUMENTS</p> <p>X: particularly relevant if taken alone Y: particularly relevant if combined with another document of the same category A: technological background O: non-written disclosure P: intermediate document</p> <p>T: theory or principle underlying the invention E: earlier patent document, but published on, or after the filing date D: document cited in the application L: document cited for other reasons &: member of the same patent family, corresponding document</p> | | | |

EPO FORM 1503 (01.82) (P0401)